



## NTN BEARING INDONESIA



5303SCZZ/5K Bearing 2D drawings and 3D CAD models

0.669 Inch | 17 Millimeter x 1.85 Inch | 47 Millimeter x 0.874 Inch | 22.2 Millimeter 0.669 Inch | 17 Millimeter x 1.85 Inch | 47 Millimeter x 0.874 Inch | 22.2 Millimeter NTN 5303SCZZ/5K Angular Contact Ball Bearings

Bearing No. 5303SCZZ/5K

|                                 |   |
|---------------------------------|---|
| Category                        | Angular Contact Ball Bearings   |
| Inventory                       | 0.0   |
| Manufacturer Name               | NTN   |
| Minimum Buy Quantity            | N/A   |
| Weight                          | 0.185   |
| Product Group                   | B00152  |
| Enclosure                       | 2 Metal Shields   |
| Flush Ground                    | No  |
| Rolling Element                 | Ball Bearing  |
| Number of Rows of Balls         | Double Row  |
| Precision Class                 | ABEC 1   ISO P0   |
| Maximum Capacity / Filling Slot | No  |
| Snap Ring                       | No  |
| Cage Material                   | Steel   |
| Contact Angle                   | 25 Degree   |
| Internal Clearance              | C0-Medium   |
| Number of Bearings              | 1 (Single)  |
| Inch - Metric                   | Metric  |
| Long Description                | 17MM Bore; 47MM Outside Diameter; 22.2MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC |



## NTN BEARING INDONESIA

|                        |   |
|------------------------|---|
|                        | 1   ISO P0; No Filling Slot;<br>No Snap Ring;<br>C0-Medium; Steel Cage; 25<br>Degree; 1 |
| Other Features         | Kyodo Yushi Multemp SRL<br>Prelubricated  |
| Category               | Angular Contact Ball<br>Bearing   |
| UNSPSC                 | 31171531  |
| Harmonized Tariff Code | 8482.10.50.28   |
| Noun                   | Bearing   |
| Keyword String         | Angular Contact   |
| Manufacturer URL       | <a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>                       |
| D                      | 1.85 Inch   47 Millimeter   |
| B                      | 0.874 Inch   22.2 Millimeter  |
| d                      | 0.669 Inch   17 Millimeter  |