



# NTN BEARING INDONESIA



3.15 Inch | 80 Millimeter x 4.921 Inch | 125 Millimeter x 1.732 Inch | 44 Millimeter NSK 7016A5TRDUMP4Y Precision Ball Bearings

Bearing No. 7016A5TRDUMP4Y

7016A5TRDUMP4Y Bearing 2D drawings and 3D CAD models

Category	Precision Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight	1.7
EAN	0029176587399
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 7   ISO P4
Material - Ball	Steel
Number of Bearings	2 (1 Pair)
Contact Angle	25 Degree
Preload	Medium
Raceway Style	1 Rib Outer Ring
Cage Material	Phenolic
Rolling Element	Ball Bearing
Mounting Arrangement	Duplex-Universal
Flush Ground	Yes
Inch - Metric	Metric
Other Features	Single Row   Angular Contact   Bore and OD are Exclusive All Others are ISO 4
Long Description	80MM Bore; 125MM Outside Diameter; 44MM Width; Open Enclosure;



## NTN BEARING INDONESIA

	ABEC 7   ISO P4 Precision; Steel Ball Material; 2 (1 Pair) Bearings; 25 Degree Contact Angle; Phenolic Cage Material; 1 Rib Outer Ring Ra
Category	Precision Ball Bearings
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact Ball
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Manufacturer Item Number	7016A5TRDUMP4Y
Weight / LBS	3.748
B	1.732 Inch   44 Millimeter
D	4.921 Inch   125 Millimeter
d	3.15 Inch   80 Millimeter
bore diameter:	80 mm
closure type:	Open
outside diameter:	125 mm
radial dynamic load capacity:	90500 N
overall width:	44 mm
precision rating:	ABEC7, P4
contact angle:	25 °
cage material:	Polyamide Cage
duplex type:	Duplex Universal
finish/coating:	Uncoated
internal clearance:	C0
fillet radius:	1.1 mm